

DOUBLE SIDED ACRYLIC TAPE (CLEAR)

DATE OF TEST: 18-01-17

ADHESIVE	TAPE COLOR(T) &	FORCE	ELONGATION	TOTAL THICKNESS
	RELEASE LINER (R.)	(N)	(%)	(UM)
Silicone Acrylic	Clear (T) PE Red Liner (R.)			1.0 mm (T)
INITIAL TACK	PEEL ADHESION (180°)	TENSILE STRENGTH	HOLDING POWER	HEAT RESISTING
(# 7)	(N/INCH)	(N)	(PER HOUR)	(MINUTE / °C)

(# = BALL) (UM = MICRON) (°C = CELSIUS) (≥ = GREATER THAN) (\leq = LESS THAN) (% = PERCENT) (N=NEWTON)

SHELF LIFE:

One year from date of receipt by customer . Please keep in cool dry place .

GENERAL DESCRIPTION:

Double Sided Acrylic Tape is a high performance, high tack bonding tape that is weather and water resistant.

APPLICATIONS:

It is used for bonding and mounting of various parts in the automotive industry, electronics industry, furniture industry and the advertising, arts and graphics applications that require bonding.

Note: All information and recommendations are given by us in good faith on the basis of practical experience, but without warranty. The user shall determine the suitability of the product and the method of application for each specific use.

IDEALTAPE SDN BHD (969219-X)

NO: 7 JALAN BALAKONG JAYA 1, TAMAN INDUSTRI BALAKONG JAYA, 43300 BALAKONG SELANGOR DARUL EHSAN, MALAYSIA.

TEL: 03-8964 0983 / 016-2100 268 FAX: 03-8964 0982 EMAIL: idealtapesb@gmail.com

WEBSITE: www.idealtape.com.my