



FLOOR MARKING TAPE

DATE OF TEST : 18-01-17

ADHESIVE	TAPE COLOR(T) & RELEASE LINER (R.)	FORCE (N)	ELONGATION (%)	TOTAL THICKNESS (UM)
Natural rubber	10 Colours	150%	150

INITIAL TACK (# 7)	PEEL ADHESION (180°) (N /INCH)	TENSILE STRENGTH (N/CM)	HOLDING POWER (PER HOUR)	HEAT RESISTING (MINUTE / °C)
.....	28	60

(# = BALL) (UM = MICRON) (°C = CELSIUS) (≥ = GREATER THAN) (≤ = LESS THAN) (% = PERCENT) (N=NEWTON)

SHELF LIFE :

One year from date of receipt by customer . Please keep in cool dry place .

GENERAL DESCRIPTION :

(PVC) film coated with an aggressive rubber-resin adhesive with good aging characteristics. are available and to suit various color marking requirements.

COLOUR : Black/White , Red/White, Yellow/Black , Green/White , Red , Blue , Black , Green , White ,Yellow)

APPLICATIONS :

- Widely used in facility aisles, equipment storage and wall storage.
- Denote the location of fire extinguishers or other fire fighting equipments.
- Marking of internal sporting courts such as volleyball court, football court as well as badminton court.
- Ideal for general purpose warning and marking such as hazard warning to increase danger awareness.

Note : All information and recommendations are given by us in good faith on the basis of practical experience, but without warranty . The user shall determine the suitability of the product and the method of application for each specific use.

IDEALTAPE SDN BHD (969219-X)

NO : 7 JALAN BALAKONG JAYA 1 , TAMAN INDUSTRI BALAKONG JAYA , 43300 BALAKONG SELANGOR DARUL EHSAN , MALAYSIA .

TEL : 03-8964 0983 / 016-2100 268 FAX : 03-8964 0982 EMAIL : idealtapesb@gmail.com

WEBSITE : www.idealtape.com.my