



# MASKING TAPE

## ( HIGH TEMPERATURE 506 )

DATE OF TEST : 18-01-17

ADHESIVE	TAPE COLOR(T) & RELEASE LINER (R.)	FORCE (N)	ELONGATION (%)	TOTAL THICKNESS (UM)
Solvent Rubber	(T)= Natural	----	7	130

INITIAL TACK (# 7)	PEEL ADHESION (180°) (N /INCH)	TENSILE STRENGTH (N)	HOLDING POWER (PER HOUR)	HEAT RESISTING (MINUTE / °C)
35 mm	2.75	27.5	≥ 5	120 (1 hour)

(# = BALL) ( UM = MICRON ) (°C = CELSIUS) ( ≥ = GREATER THAN) ( ≤ = LESS THAN) (% = PERCENT) (N=NEWTON)

### SHELF LIFE :

Eight months from date of receipt by customer . Please keep in cool dry place .

### GENERAL DESCRIPTION :

- Rubber based adhesive for excellent holding strength.
- Good tackiness and adhesion strength.
- Easy unwind .
- Crepe paper backing conforms to irregular surfaces.
- Clean and residue free removal.

### APPLICATIONS :

Adhesive for high temperature application. Application such as automotive paint spraying, electroplating and etc.

Note : All information and recommendations are given by us in good faith on the basis of practical experience, but without warranty . The user shall determine the suitability of the product and the method of application for each specific use.

### IDEALTAPE SDN BHD (969219-X)

NO : 7 JALAN BALAKONG JAYA 1 , TAMAN INDUSTRI BALAKONG JAYA , 43300 BALAKONG SELANGOR DARUL EHSAN , MALAYSIA .

TEL : 03-8964 0983 / 016-2100 268 FAX : 03-8964 0982 EMAIL : idealtapesb@gmail.com

WEBSITE : www.idealtape.com.my