



MASKING TAPE

(HIGH TEMPERATURE M 502)

DATE OF TEST : 18-01-17

| ADHESIVE | TAPE COLOR(T) & RELEASE LINER (R.) | FORCE (N) | ELONGATION (%) | TOTAL THICKNESS (UM) |
|----------------|------------------------------------|-----------|----------------|----------------------|
| Solvent Rubber | (T)= Natural | ---- | 8 | 145 |

| INITIAL TACK (# 7) | PEEL ADHESION (180°) (N /INCH) | TENSILE STRENGTH (N) | HOLDING POWER (PER HOUR) | HEAT RESISTING (MINUTE / °C) |
|--------------------|--------------------------------|----------------------|--------------------------|------------------------------|
| 15 mm | 3.14 | 31.4 | | 150 (1 hour) |

(# = BALL) (UM = MICRON) (°C = CELSIUS) (≥ = GREATER THAN) (≤ = LESS THAN) (% = PERCENT) (N=NEWTON)

SHELF LIFE :

Eight month from date of receipt by customer . Please keep in cool dry place .

GENERAL DESCRIPTION :

- Proprietary cured rubber based adhesive for excellent holding strength.
- Excellent tackiness with good adhesion to metals and plastic such as pp,pu and abs .
- Crepe paper backing conforms to irregular surfaces.
- Solvent and moisture resistance to minimize bleed-through.
- Clean and residue free removal.

APPLICATIONS :

Adhesive for high temperature application. Application such as automotive paint spraying,bandoleering,electroplating and etc.

Note : All information and recommendations are given by us in good faith on the basis of practical experience, but without warranty . The user shall determine the suitability of the product and the method of application for each specific use.

IDEALTAPE SDN BHD (969219-X)

NO : 7 JALAN BALAKONG JAYA 1 , TAMAN INDUSTRI BALAKONG JAYA , 43300 BALAKONG SELANGOR DARUL EHSAN , MALAYSIA .

TEL : 03-8964 0983 / 016-2100 268 FAX : 03-8964 0982 EMAIL : idealtapesb@gmail.com

WEBSITE : www.idealtape.com.my