



PVC INSULATION TAPE

DATE OF TEST : 18/01/2017

ADHESIVE	TAPE COLOR(T) & RELEASE LINER (R.)	BACKING THICKNESS (µm)	ELONGATION (%)	TOTAL THICKNESS (MM)
Natural rubber	6 colours	110 ± 6	≥ 180	0.13 ± 0.01

INITIAL TACK (# 7)	ADHESIVE STRENGTH (N/MM)	TENSILE STRENGTH (N/CM)	DIELECTRIC STRENGTH (KV)	HEAT RESISTING (MINUTE / °C)
----	≥ 3.0N / 25mm (GB/T8792-1998)	Md -----≥ 18 Td -----≥ 12	≥ 5	----

(# = BALL) (UM = MICRON) (°C = CELSIUS) (≥ = GREATER THAN) (≤ = LESS THAN) (% = PERCENT) (N=NEWTON)

SHELF LIFE :

One year under the condition of 23°C and 50% Relative Humidity

GENERAL DESCRIPTION :

- Adopts soft PVC film as the base material and coating special rubber type pressure sensitive adhesive
- Features good insulation resistance , good flame retardent, voltage resistance and cold resistance .
(COLOUR : Black / Red / Blue / Yellow / Green / White)

APPLICATIONS :

- Applied for integral wiring harness wire winding , insulation protection , demagnetizing loop and telecommunication wiring and more .

Note : All information and recommendations are given by us in good faith on the basis of practical experience, but without warranty . The user shall determine the suitability of the product and the method of application for each specific use.

IDEALTAPE SDN BHD (969219-X)

NO : 7 JALAN BALAKONG JAYA 1 , TAMAN INDUSTRI BALAKONG JAYA , 43300 BALAKONG SELANGOR DARUL EHSAN , MALAYSIA .

TEL : 03-8964 0983 / 016-2100 268 FAX : 03-8964 0982 EMAIL : idealtapesb@gmail.com

WEBSITE : www.idealtape.com.my